

ANGOLO

Electromechanical automations for swing gates





NET24N 24V d.c. operators with control board

COD.	Art.	EN			OTHER CHARACTERISTICS
626300	ANGOLO 24NET/1	EN 12453 IN COMPLIANCE WITH STANDARDS EN 12445	•	NET24N	<ul style="list-style-type: none"> - 1 operator - Anti-crushing safety device - Speed adjustment during normal cycle and slow down in opening and closing
626310	ANGOLO 24NET/2	EN 12453 IN COMPLIANCE WITH STANDARDS EN 12445	•	NET24N	<ul style="list-style-type: none"> - 2 operators - Anti-crushing safety device - Speed adjustment during normal cycle and slow down in opening and closing

All models have: arm and mounting plate not included (see on page 64)

DIMENSIONS WITH ARMS



Refer to instructions manual for installation dimensions

DIAGRAM WITH ARTICULATED ARM




DIAGRAM WITH SLIDING ARM




If the leaf length is bigger than 2 meters or if you use reversible models you must install the electric-lock to block the gate in closed position


The height and the leaf structure, as well as the presence of strong wind, can cause the reduction of the value of the data contained in table.

TECHNICAL INFO	ANGOLO 24NET
Motor power supply (V)	24 DC
Maximum power absorption (W)	60
Max thrust (N)	120
Duty cycle (cycles/hours)	25
N. max cycles in 24h.	60


TECHNICAL INFO	ANGOLO 24NET
Operating temperature (°C)	-20 ÷ 50
90° Opening time (s)	15
Weight with packing (Kg)	12,5
Protection degree	IP44










EXAMPLE OF A TYPICAL INSTALLATION




DIMENSIONS



 <p>Cod. 626010 Art. ANGOLO 24NET/2 Electromechanical operator for swing gates</p>	 <p>Cod. 629160 Art. 580A Aluminium articulated arm</p>	 <p>Cod. 662030 Art. 104LUX Pair of adjustable (15°) surface mounted photocells</p>
 <p>Cod. 664000 Art. PILLY/60 Pair of aluminium columns for photocells, height 55 cm.</p>	 <p>Cod. 663030 Art. 102LUX Keyswitch with two contacts, flush mounted. Supplied with 2 keys.</p>	 <p>Cod. 661082 Art. LED24AI Led flashing light 24V with built-in antenna 433Mhz</p>
 <p>Cod. 672580 Art. TR2 Remote control Black version art. TR2N also available (page 118)</p>	 <p>Cod. 381060 Art. 580V Vertical mounting plate</p>	 <p>Cod. 668010 Art. 127 Warning sign</p>

SPECIFIC ACCESSORIES



OTHER ACCESSORIES

