

Ins-30161 PROXIMITY panel mount reader EM4100 Wiegand output

Technical Support


☎ 01273 811011

✉ support@paxton.co.uk


Technical help is available: Monday - Friday from 07:00 - 19:00 (GMT)
Saturday from 09:00 - 13:00 (GMT)

Documentation on all Paxton products can be found on our website - <http://www.paxton.co.uk/>

Fitting



Wiring



Cable extensions

Readers can be extended using Belden CR9540 10-core overall screened cable to a maximum of 100 metres.

Suitability

Security-sensitive doors



Mounted on metal surface



Wet environments



Readers mounted together



Specifications

Electrical	Min	Max	
Voltage	9V DC	14V DC	
Current		110 mA	
Carrier frequency			125 kHz
Wiegand format			26 bits
Environment	Min	Max	
Operating temperature	-20 °C	+55 °C	
Waterproof	IPX7		Outdoor Use
Cable length			5 metres
Dimensions	Width	Height	Depth
Panel mount reader	58 mm	58 mm	17 mm
Window size	40 mm	40 mm	
Mounting holes - 3.7 mm dia - square formation	49 mm	49 mm	See front page for position



The declaration of conformity is available on request. Contact details are provided at: <http://paxton.info/596>

This product is not suitable for retail sale. All warranties are invalid if this product is not installed by a competent person.

Ins-30161 PROXIMITY panel mount reader EM4100 Wiegand output

Technical Support


 01273 811011

 support@paxton.co.uk


Technical help is available: Monday - Friday from 07:00 - 19:00 (GMT)
Saturday from 09:00 - 13:00 (GMT)

Documentation on all Paxton products can be found on our website - <http://www.paxton.co.uk/>

Fitting



Wiring



Cable extensions

Readers can be extended using Belden CR9540 10-core overall screened cable to a maximum of 100 metres.

Suitability

Security-sensitive doors



Mounted on metal surface



Wet environments



Readers mounted together



Specifications

Electrical	Min	Max	
Voltage	9V DC	14V DC	
Current		110 mA	
Carrier frequency			125 kHz
Wiegand format			26 bits
Environment	Min	Max	
Operating temperature	-20 °C	+55 °C	
Waterproof	IPX7		Outdoor Use
Cable length			5 metres
Dimensions	Width	Height	Depth
Panel mount reader	58 mm	58 mm	17 mm
Window size	40 mm	40 mm	
Mounting holes - 3.7 mm dia - square formation	49 mm	49 mm	See front page for position



The declaration of conformity is available on request. Contact details are provided at: <http://paxton.info/596>

This product is not suitable for retail sale. All warranties are invalid if this product is not installed by a competent person.