



6741W

MINI HANDSFREE WIFI MONITOR, S2



Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. It is equipped with a Wi-Fi port to allow calls forwarding to mobile devices. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies.

Equipped as standard with 8 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard.

Complete with 2 x 8-position dip-switch for user code programming and button programming. The wall-mounting backplate and riser distribution terminal art. 1214/2C are included. The monitor can only be used in 2-wire system Simplebus 2. Dimensions: 115x160x22mm.

AWARDS



CERTIFICATIONS



The technical specifications are subject to variations without warning.



6741W

MINI HANDSFREE WIFI MONITOR, S2

GENERAL DATA

Product height (mm):	160
Product width (mm):	115
Product depth (mm):	22
Product weight (g):	400
Product color:	White RAL9003
Material:	ABS
Desk base-mounted:	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C:	Yes
Audio/video Simplebus 2 with power supply art. 1210:	Yes
Simplebus 2 audio/video kit with power supply art. 1209:	Yes

DISPLAY FEATURES

Size (inches):	4.3
Aspect Ratio:	16:9
Resolution (pixels):	480x272

AUDIO FEATURES

Type:	Hands-free
Microphone:	6mm (ø), omnidirectional
Loudspeaker:	36mm (ø), 40 ohm, 1W

ELECTRICAL CHARACTERISTICS

Type of power supply:	Power supply from video door entry bus
Supply voltage:	22÷34VDC (bus)
Stand-by absorption (W):	0.1
Stand-by absorption in kit mode (W):	1.9
Maximum absorption (W):	8.1

HARDWARE FEATURES

Type of buttons:	Capacitive
Service buttons:	Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions:	4
Terminals:	L L CFP1 CFP2
Removable terminals:	Yes

SETTINGS

Loudspeaker volume:	Yes
---------------------	-----

The technical specifications are subject to variations without warning.



6741W

MINI HANDSFREE WIFI MONITOR, S2

SETTINGS

Ringtone volume:	Yes
Screen brightness:	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Encryption and authentication method supported:	TKIP WPA2-PSK, AES WEP 64 bits (5-digit ASCII or 10 hexadecimal codes), WEP 128 bits (13-digit ASCII or 26 hexadecimal codes), WPS authentication (supported for WPA2-PSK)
IP address assignment:	DHCP
IoT connection to Comelit Cloud:	Yes
Firmware update via Comelit Cloud:	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree:	IP30
Operating temperature (°C):	5 ÷ 40
Operating humidity (RH max - %):	25 ÷ 75
Environmental class:	I
Compliance and Certifications:	RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS

Compatibility with Comelit app:	Yes
Door opener:	Yes
Self-ignition:	Yes
Intercom calls:	Yes
Actuator control:	Yes
CPS call:	Yes
Outside door call input:	Yes
"Silent" mode (Privacy):	Yes
Video memory:	Yes
Door opening on call (Doctor):	Yes
Automatic answer (handsfree):	Yes
Door open signaling:	Yes
Multiple address:	Yes
Customizable ringtone:	Yes
Date/time display:	Yes



6741W

MINI HANDSFREE WIFI MONITOR, S2

MAIN FUNCTIONS

Sending alarm calls:	Yes
----------------------	-----



6741W

MINI HANDSFREE WIFI MONITOR, S2

ACCESSORIES



6711WV

ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.



6732A

DESK BASE FOR HANDS-FREE MINI MONITOR. S2

Desk base installation accessory for hands-free Mini monitor in Simplebus 2 system.



6720

Access. cables external passage for MINI HF. S2

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables.