



STAINLESS STEEL ILLUMINATED BUTTON

EXIT BUTTONS

Market leading exit buttons, that is both hard wearing and cost effective. Suitable for use in external and internal applications.



K-ILH-GS/PTE



K-ILH-GS/DR



K-AP-ILH-GS/PTE

SPECIFICATION

- K-ILH-__
- Contacts: NO/NC
 - Double Pole / Double Throw
 - Contact rating: 5A @240VAC
 - Contact resistance: <50mΩ
 - Voltage: 12-24VDC
 - Wear resistant legend
 - Security screws (allen key type)
 - Internal or External use
 - Button is rated at IP65
 - Operating temperature: -10C to +50C

FEATURES

- K-ILH-__
- Stainless steel illuminated button
 - Momentary operation
 - LED status:
 - Green (Static)
 - Flush fitting as standard
 - Fits on standard RGL Surface Boxes
 - Ideal for general/sensitive areas
 - Distance between fixing holes 60mm

The product can be made up with various different plates within the RGL range.

OTHER PRODUCTS

WP66-G-ILG/GR



TLI45



SPX-26M



DIMENSIONS

- K-ILH-__
- 85H x 85W x 28D (mm)
 - 300g (Boxed)
 - 260g (Unboxed)

CONTENTS

- K-ILH-__
- Illuminated Switch
 - Stainless Steel Plate (2mm)
 - 2 Security Screws
 - Allen Key
 - Electrical Back Box



Manufactured by a BSIA Member

CDL-300

