

WIRELESS WIFI NVR KIT

7" Touch Screen
with 2 WiFi Cameras

EasyGates Direct



Product Description

The 7" high-definition touch screen network video recorder is designed with lightweight and easy to place. It can support 4 channels of real-time input at the same time, support motion detection recording, and store video in TF card.

- 1CH playback
- Supports dual WIFI
- Supports IOS, Android mobile APP remote access, remote playback and alarm push function.
- Camera can connect recorder through wireless code match.
- NVR can support 4CH of 2MP, H264/H265 pure wireless camera input, battery camera and doorbell.



SPECIFICATION	LCD-KIT2MP
7" HD TOUCH SCREEN NETWORK RECORDER SPECIFICATION	
Operating System	Embedded Linux operating system
Video Input	4 channels x 1080P, pure wireless camera
Video Output	Size: 7" Resolution: 1024 x600 Supports touch screen operation
Audio Input	Built-in mic-phone, supports voice intercom with IPC
Audio Output	Supports speaker output (built-in speaker)
VIDEO CODING PARAMETERS	
Video Compression Standard	Standard H.264, H265
Video and Playback Performance	4 channel 1080P video 1 channel 1080P playback
Video Bit Rate	256 Kbps -- 3.0 Mbps
Dual Code Stream	Support
Audio Compression Standard	AAC
VIDEO MANAGEMENT	
Video Mode	PIR motion detection recording, automatic overlay loop recording
STORAGE METHOD	
Video Storage Method	TF card recording storage
EXTERNAL INTERFACE	
Battery Switch	Select the power supply to NVR by built-in battery or DC jac
USB Interface	1 USB 2.0 interface (supports USB flash drive upgrade, and mouse)
2.4G Dual WIFI Interface	Support IPC code and connection, and wireless Internet access
TF Card Holder	Maximum support 128G
OTHER	
Power Supply	DC 5V 2.5A
Power Consumption	≤8.0W
Working Temperature	-10°C ~ +50°C
Machine Size	191 x 123 x 31.5mm
Machine Weight	≤500g

WIRELESS WIFI NVR KIT

7" Touch Screen
with 2 WiFi Cameras

EasyGates Direct



SPECIFICATION	LCD-KIT2MP
CAMERA SPECIFICATION	
Sensor	2MP 1/2.9" 1/3" CMOS sensor
Light Sensor	Light sensor resistance
IR-Cut	Supported
Lens	4mm
Mix Luxury	Black white 0 Lux
IR Light	6pcs array ir light / suggested use in 5-10m
Light Mode	Day / night / black white / auto
INTERFACE	
Audio Input	Built-in mic
Audio Output	Built-in speaker
Reset	With reset button/used to match code/reset
wifi	Built in 2.4G antenna
TF Card	Supports : max 128G
RJ45 Interface	10-100M self-adaptive
Indicator Light	At bottom of cable/LED flash means AP mode/LED keep light means connection well
COMPRESS STANDER	
Video Compress Stander	H.264 Main Profile
Audio Compress Stander	AAC
IMAGE/CODE STREAM	
Resolution	1920 x 1080 (1080P)
Code Steam	1920 x 1080@15F main stream 640 x 360@15F sub stream
OSD	Supported
INTERNET	
Internet Protocol	TCP / IP / HTTP / ICMP / UDP / ARP / IGMP /DHCP / DNS / NTP / RTSP
Onvif	V2.4
ENVIRONMENT	
Working Temperature/Moisture	-20°C ~ +50°C / 20% ~ 80%
Consumption	12V-1A DC
Power In	3W
OTHERS	
PIR	Suggested use in 7meter in 60° area