



6601W

ICONA MONITOR, S2



SB1

Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 Colour systems. Dimensions 5.6"x5.7"x0.9".

AWARDS





6601W

ICONA MONITOR, S2

GENERAL DATA

Product height (mm)	147
Product width (mm)	143
Product depth (mm)	23
Product weight (g)	500
Product color	White RAL9003, base grey RAL7001
Material	ABS, Glass
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY FEATURES

Size (inches) (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272

AUDIO FEATURES

Type	Hands-free
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (Ø) x 20 (H)mm, 8 ohm, 2W
Technologies implemented	Full-Duplex

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
----------------------	--



6601W

ICONA MONITOR, S2

ELECTRICAL CHARACTERISTICS

Supply voltage	22÷34 VDC (Bus)
Maximum absorption (W)	10.8

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Door open
No. of programmable buttons for additional functions	5
Clamps	L L - + CFP1 CFP2 S+ S- In1 In2
Removable terminals	Yes
Number of inputs (n°)	2

SETTINGS

Loudspeaker volume	Yes
Ringtone volume	Yes
Screen brightness	Yes
Screen contrast	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max - %) (%)	25 ÷ 75
Environmental class	I
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes



6601W

ICONA MONITOR, S2

MAIN FUNCTIONS


Outside door call input	Yes
Output for call repetition	Yes
Silent mode (Privacy)	Yes
Door opening on call (Doctor)	Yes
Automatic answer (handsfree)	Yes
Door open signaling	Si
Customisable ringtone	Yes
Sending alarm calls	Yes



6601W

ICONA MONITOR, S2

ACCESSORIES



6612A **DESK BASE FOR ICONA MONITOR**

Desk base installation accessory for Icona monitor. Dimensions 105x70x110mm.



6617 **Flush-mounted box for plasterboard. Icona**

Flush-mount box allowing mounting of Icona series monitors on plasterboard and/or cement walls. Dimensions: 129x129x50 mm



6620 **WALL BRACKET FOR ICONA MONITOR**

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.



6118 **PLANUX, SMART, ICONA CLIPS FOR DRY LINED WALLS**

Installation kit for plasterboard walls for Planux, Smart and Icona monitors.



6117 **FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS**

The accessory can be used for the tilt-adjustment fitting of art. 6122. Dimensions: 132X132X50 mm.