



KVS2011KP

SWITCH VIDEO KEYPAD KIT-MINI HF WI-FI. S2



Single-family kit with flush-mounted Switch entrance panel with 1 button and electronic key keypad and Mini Handsfree monitor with Wi-Fi that allows you to answer video entry phone calls from anywhere. Pre-configured and ready to use. Can be expanded up to 4 internal units. Simplebus2 system.



KVS2011KP

SWITCH VIDEO KEYPAD KIT-MINI HF WI-FI. S2

KIT PRODUCTS



IX0101KP SWITCH FACEPLATE, 1 BUT. + ELECTRONIC KEY

Front plate for Switch entrance panel with electronic keypad in 2.5 mm thick brushed AISI 316 stainless steel. Adapter art. 1250U (supplied) offers the option of using the audio or audio/video module - not supplied - depending on the type of wiring applied (Simplebus digital 2-wire or ViP). Complete with 1 pre-fitted, pre-wired button. White LED nameplate backlighting. Nameplate replacement from the front. Protection rating IK08. To be finished with flush-mounted box or surface-mounted casing (not supplied). Dimensions (L x H x P): 150 x 262.7 x 2.5 mm.

GENERAL DATA

Type	Monoblock
Product height (mm)	262.7
Product width (mm)	150
Product depth (mm)	2.5
Product colour	Steel
Material	Stainless steel AISI 316
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory



KVS2011KP

SWITCH VIDEO KEYPAD KIT-MINI HF WI-FI. S2



6741W 2 WIRES MINI HANDSFREE WI-FI DOOR ENTRY MONITOR

Hands-free Mini Wif-Fi door entry monitor for Simplebus2 system. When used in conjunction with the Comelit app (available to download free of charge from the Google and Apple stores) and/or the Alexa voice assistant, it can be used to answer calls directly from your smartphone/tablet/Alexa device, both locally and remotely. It can be used to enable the “Face recognition” function directly from the app, to automatically - once a person has been recognised - send a lock-release command (enabled by default), trigger an actuator to control a light or additional opening and receive notification when a known individual makes a call. Replacing an old door entry monitor to benefit from all the advantages offered by Wi-Fi technology is no longer problematic: Mini Wi-Fi is actually compatible with all types of Comelit Simplebus 2 video entry phone system and does not require any additional masonry work. Supplied with mounting backplate and riser distribution terminal art. 1214/2C.

GENERAL DATA	
Product height (mm)	160
Product width (mm)	115
Product depth (mm)	22
Product weight (g)	400
Product color	White RAL9003
Material	ABS, Polycarbonate Makrolon 2407, Anodized aluminum
Flush-mounted	No
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory