


Technical Support

 01273 811011

 support@paxton.co.uk


Technical help is available: Monday - Friday from 07:00 - 19:00 (GMT)
Saturday from 09:00 - 13:00 (GMT)

Documentation on all Paxton products can be found on our website - <http://www.paxton.co.uk/>

Fitting



Wiring



Cable extensions

Readers can be extended using Belden CR9540 10-core overall screened cable to a maximum of 100 metres.

Suitability

Security-sensitive doors



Mounted on metal surface



Wet environments



Readers mounted together



Specifications

Electrical	Min	Max	
Voltage	10V DC	14V DC	
Current		110 mA	
Carrier frequency			125 kHz
Wiegand format			26 bit
Environment	Min	Max	
Operating temperatures - all items	- 35 °C	+ 66 °C	
Waterproof		IPX7	
Cable length			5 metres
Dimensions	Width	Height	Depth
	76 mm	76 mm	27 mm



The declaration of conformity is available on request. Contact details are provided at: <http://paxton.info/596>

This product is not suitable for retail sale. All warranties are invalid if this product is not installed by a competent person.

Technical Support

📞 01273 811011

✉️ support@paxton.co.uk


Technical help is available: Monday - Friday from 07:00 - 19:00 (GMT)
Saturday from 09:00 - 13:00 (GMT)

Documentation on all Paxton products can be found on our website - <http://www.paxton.co.uk/>

Fitting



Wiring



Cable extensions

Readers can be extended using Belden CR9540 10-core overall screened cable to a maximum of 100 metres.

Suitability

Security-sensitive doors



Mounted on metal surface



Wet environments



Readers mounted together



Specifications

Electrical	Min	Max	
Voltage	10V DC	14V DC	
Current		110 mA	
Carrier frequency			125 kHz
Wiegand format			26 bit
Environment	Min	Max	
Operating temperatures - all items	- 35 °C	+ 66 °C	
Waterproof		IPX7	
Cable length			5 metres
Dimensions	Width	Height	Depth
	76 mm	76 mm	27 mm



The declaration of conformity is available on request. Contact details are provided at: <http://paxton.info/596>

This product is not suitable for retail sale. All warranties are invalid if this product is not installed by a competent person.