## **DDA COMPLIANT VIDEO INTERCOM** Coded Keypad



02-0200-EN DDA compliant video intercom: coded keypad (yellow rings on buttons), dial per flat number, access control square reader - Flush fit





REMOTE ONLINE MANAGEMENT www.intratone.com

CENTRAL UNIT	<b>1 DOOR</b> (03-0102-EN)	2 DOORS (03-0101-EN)
MAX. NUMBER OF HOMES MANAGED	max. 100	max. 1,000
SYSTEM		
Number of relays	1 (+3)	2 (+2)
CONNECTION		
3G unit Intratone (mobile networks)	•	•
3G UNIT SPECIFICATIONS		
Remote 3G unit	•	•
CALLS/UPDATES INCLUDED	Request quotation	Request quotation
ACCESS CONTROL EQUIPMENT		
ACCESS CONTROL EQUIPMENT Coded keypad	•	•
	•	•
Coded keypad	• • •	•
Coded keypad Trade button	• • •	•
Coded keypad Trade button Square proximity reader	• • • •	•
Coded keypad Trade button Square proximity reader FITTING	• • •	• • •

Call length Configurable welcome message (64 scrolling or static characters) Simplified calling for the partially sighted Call sheet display (apartments) during time slots Operational messages: (call in progress) Speech synthesis + display Anti-disturbance <sup>(1)</sup> Sound level adjustment without dismantling (depending on associated central unit) Automatic call return if no answer	40 sec. YES YES YES YES YES YES

<sup>(1)</sup> System ensuring that a resident is not disturbed by repetitive calls

## **TECHNICAL SPECIFICATIONS**

POWER SUPPLY	CABLING		INTERCOM SIZE	ENVIRONMENT
Central unit min. 12/24 V DC - 2 A	2-DOOR CENTRAL UNIT 03-0101-EN 3G unit - Central unit 6 wires (3 twisted pairs) Ø 0.8 mm - Max: 100 m Central unit - Intercom 6 wires (3 twisted pairs) Ø 0.8 mm - Max: 200 m Intercom - 3G unit 2 wires (1 twisted pair) Ø 0.8 mm - Max: 100 m	1-DOOR CENTRAL UNIT 03-0102-EN Central unit - Intercom / 3G unit 4 wires (2 twisted pairs) Ø 0.8 mm - Max: 200 m Intercom - 3G unit 6 wires (3 twisted pairs) Ø 0.8 mm - Max: 100 m	L x H x D 180 x 385 x 2.5 mm	Intercom operating temperature -20°C to +70°C Intercom storage temperature -20°C to +70°C Intercom protection class Intercom IP55 Outdoor fitting

## **DDA COMPLIANT AUDIO INTERCOM - FLUSH FIT**

REFERENCES	INTERCOMS ONLY	OUR PRICES
02-0200-EN	Stainless steel	
	COMPLETE PACKS INCLUDING 1 INTERCOM + 1 x 100-NAMES CENTRAL UNIT (1-door central unit 03-0102-EN)	
02-0201-EN	Stainless steel	
	COMPLETE PACKS INCLUDING 1 INTERCOM + 1 x 1.000-NAMES CENTRAL UNIT (2-door central unit 03-0101-EN)	
02-0202-EN	Stainless steel	
	ACCESSORIES	
12-0131	Surface mounted box for DDA compliant video intercom - Stainless steel	



## **BASIC DIAGRAM**

