DIGITAL NOTICE BOARD



- No more paper notifications in entrance halls
- Inform residents in Real-time, without having to go on site
- Communication to all or some notice boards

Digital notice board, 15-inch screen





CONNECTION	
3G data unit (06-0112)	•
Number of notice boards per 3G unit	1
MANAGEMENT / UPDATES	
Via the management site www.intratone.info	•
Format of downloaded documents	PDF, Excel, Word
File size	8 MB
UNLIMITED UPDATES	•
FITTING	
Flush-fit / indoors	11-0102-XX
Surface-mounted / indoors / outdoors	11-0101-XX
Surface-mounted / outdoors	11-0103-XX
FINISH	
Grainy dark blue	





TECHNICAL SPECIFICATIONS

POWER SUPPLY		
Notice board, 24 V DC		
2 A - indoor version		
3 A - outdoor version		

CABLING Notice board – 3G unit 4 wires (2 twisted pairs) Ø 0.8 mm Max. distance: 100 m

Indoor version – Surface-mounted 348 mm x 525 mm x 40 mm Version for integration – Flush-fit 350 mm x 510 mm x 42 mm Outdoor version – Surface-mounted 348 mm x 549 mm x 49 mm

INTERCOM SIZE

ENVIRONMENT

Notice board, indoor version Operating temperature 0°C to + 50°C Storage temperature -20°C to + 70°C Protection class: IP52 Notice board, outdoor version Operating temperature -20°C to +70°C Storage temperature -30°C to +70°C Protection class IP65 Waterproof Outdoor fitting

DIGITAL NOTICE BOARDS RANGE

REFERENCES	15-INCH COLOUR SCREEN	OUR PRICES
11-0101-XX	Indoor version - Surface-mounted	
11-0102-XX	Flush-fit - To be integrated into a post, for example.	
11-0103-XX	Outdoor version - Surface-mounted	
ACCESSORY		
06-0133-XX	Intrabox Notice Board 15 Years Prepaid Communication : Mini quantities : 10 PCS - Surface mounted display panel - Indoor Version (11-0101-XX) - 3G / Data Module with 15 years of prepaid communication. ONLY ON REQUEST	

BASIC DIAGRAM

Diagram 1: simplified wiring

