



"RENO" INTERCOMS



"RENO" Intercom with name-scrolling, 12-key backlit coded keypad and proximity reader - Flush-fit



REMOTE ONLINE MANAGEMENT
www.intratone.com

CENTRAL UNIT	1 DOOR (03-0102-EN)	2 DOORS (03-0101-EN)
MAX. NUMBER OF HOME MANAGED SYSTEM	100	1 000
CONNECTION		
3G / 3G-IP Intratone unit (mobile networks)	•	•
3G / 3G-IP UNIT SPECIFICATIONS		
Remote 3G / 3G-IP unit	•	•
Connection to an additional camera (remote)	•	•
Number of video intercoms per 3G unit	1	2
Number of video intercoms per 3G-IP unit	1	1
CALLS / UPDATES INCLUDED	Request quotation	Request quotation
ACCESS CONTROL EQUIPMENT		
Coded Keypad	•	•
Proximity reader	•	•
FITTING		
Flush-fit	•	•
FINISH		
Anthracite / Silver	•	•
Platinum / Silver	•	•
Gilded / Gold	•	•

MORE INFO:
see pages 52 and 53
CENTRAL UNITS

Call length	40 sec.
Configurable welcome message (64 scrolling or static characters)	YES
Fast alphabetical search	YES
Simplified calling for the partially sighted	YES
Call sheet display (apartments) during time slots	YES
Operational messages: (call in progress...) Speech synthesis + display	YES
Anti-disturbance ⁽¹⁾	YES
Sound level adjustment without dismantling (depending on associated central unit)	YES
Automatic call return if no answer	YES

⁽¹⁾ System ensuring that a resident is not disturbed by repetitive calls

TECHNICAL SPECIFICATIONS

POWER SUPPLY	CABLING	INTERCOM SIZE	ENVIRONMENT	
Central unit min. 12/24 V DC - 2 A	2-DOOR CENTRAL UNIT 03-0101-EN 3G unit - Central unit 6 wires (3 twisted pairs) Ø 0.8 mm - Max: 100 m Central unit - Intercom 6 wires (3 twisted pairs) Ø 0.8 mm - Max: 200 m Intercom - 3G unit 2 wires (1 twisted pair) Ø 0.8 mm - Max: 100 m	1-DOOR CENTRAL UNIT 03-0102-EN Central unit - Intercom / 3G unit 4 wires (2 twisted pairs) Ø 0.8 mm - Max: 200 m Intercom - 3G unit 6 wires (3 twisted pairs) + 2 wires (video) Ø 0.8 mm - Max: 100 m	INTERCOM SIZE L x H x D 120 x 270 x 15 mm (+ Proximity reader: 4.5 mm) BUILT-IN WALL BOX SIZE L x H x D 96 x 244 x 45 mm	ENVIRONMENT Intercom operating temperature -20° C to +70° C Intercom storage temperature -20° C to +70° C Intercom protection class Intercom IP55 Outdoor fitting

"RENO" INTERCOM RANGE

REFERENCES	INTERCOM ONLY	OUR PRICES
02-0126-EN	Anthracite / Silver	
02-0135-EN	Platinum / Silver	
02-0138-EN	Gilded / Gold	
COMPLETE PACKS INCLUDING 1 INTERCOM + 1X100-NAME CENTRAL UNIT (1-DOOR CENTRAL UNIT 03-0102-EN)		
02-0127-EN	Anthracite / Silver	
02-0136-EN	Platinum / Silver	
02-0139-EN	Gilded / Gold	
COMPLETE PACKS INCLUDING 1 INTERCOM + 1X1.000-NAME CENTRAL UNIT (2-DOOR CENTRAL UNIT 03-0101-EN)		
02-0128-EN	Anthracite / Silver	
02-0137-EN	Platinum / Silver	
02-0140-EN	Gilded / Gold	
ACCESSORIES		
12-0134	Surface-mounted box for "Reno" intercom Anthracite / Silver	
12-0140	Surface-mounted box for "Reno" intercom Platinum / Silver	
12-0141	Surface-mounted box for "Reno" intercom Gilded / Gold	

Monthly

Classic monthly packages
AUDIO or BOXEO
Unlimited calls and updates

Custom

Adjustable packages
PREPAID or FLEET
Unlimited calls and updates

SIMPLIFIED DIAGRAM

