


LM130EVF MYQ DC GARAGE DOOR OPENER

Maintenance-free, ultra-quiet including safety sensors and LED light.

KEY FEATURES



SPACE-SAVING

Design maximizes versatility

LED LIGHT

LED turns on with activation

HEAVY LIFTING

For doors up to 200 kg

MYQ

Built In



SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

BELT DRIVE SYSTEM FOR POWERFUL PERFORMANCE.

SOFT-START AND SOFT-STOP FOR SMOOTH OPERATION.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

QUIET AND RELIABLE

QUIET DC MOTOR ELIMINATES NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

HEAVY-LIFTING POWER OPERATES DOORS UP TO 200 KG.

MAINTENANCE-FREE BELT DRIVE ENSURES QUIET & DURABLE OPERATION.

WARRANTY MOTOR: 10 YEARS, CONTROL BOARD: 5 YEARS, ACCESSORIES: 2 YEARS.

SECURE & SAFE

AUTOMATIC GARAGE DOOR OPENERS IMPEDE UNAUTHORIZED ACCESS TO THE GARAGE.

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

EVOLUTION RADIO (SECURITY+ 2.0®) SENDS A NEW CODE WITH EVERY REMOTE CLICK.

AUTOMATIC FORCE SETTING & OBSTACLE DETECTION.

FAILSAFE INFRARED SENSOR AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

INCLUDED ACCESSORIES:

4-CHANNEL REMOTE CONTROL

Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4EVF

2-BUTTON WIRELESS WALL CONTROL

Operates up to 2 openers. Control your garage door without a remote control.



128EV

FAILSAFE SAFETY SENSOR KIT

Incl. wall mount and cables. LED indicates the IR sensors continuity.



771EVK

POWERFUL ADD-ONS:

INTERNET GATEWAY

MyQ technology that connects to the internet and allows monitoring and control of the garage door opener.



828EV

GARAGE DOOR MONITOR

MyQ enabled technology allows monitoring and closing up to four garage doors from any room in the house.



829EV

WIRELESS KEYPAD

Provides convenient, secure access from outside the garage with a 4-digit PIN, temporary PIN possible.



747EV

LED FLASHING LIGHT

Lamp flashes while the drive is in action. Applicable for all garage door and gate door openers.



FLA1-LED

MASTERFUL ENGINEERING.

MOTOR



- Heavy-Duty 24 V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Operating Temperature: -30°C to 55°C

POWER

- 230-240 V AC
- 50/60 Hz Voltage
- 0.8 W Stand-by Power
- 80 cm Power Cord (Euro plug)¹

MECHANICS

- High Quality Chassis and Cover
- Reliable & Quiet Belt Drive Mechanism
- Automatic Force Setting
- Electronic Limits for Easy Setup
- Maintenance-Free Operation thanks to Belt Drive
- 90° Rotation of Power Head for Space Saving



Max. 130 mm


Per second for door to move upward

Max. 130 mm

Per second for door to move downward

STANDARD SPECS.

EVOLUTION RADIO (Security+ 2.0®)



- 4-Button Remote Control (TX4EVF)
- Remote Control: 868 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 433 and 868 MHz
- Copy-Protected Coding

MyQ RADIO



- Provides 2-way communication from garage door opener and MyQ accessories.
- Enables monitoring and control of garage door openers controls via smartphone, tablet or computer.
- Receiver with 180 memory registers.

HOMELINK® COMPATIBLE (VERSION V OR SOFTWARE REV. 8)²

LIGHTING LED LIGHT



- LED turns on with activation
- Turns off 2.5 minutes after operation
- 0.8 W Stand-by Power

SHIPPING.

SHIPPING WEIGHT (in kg)



CARTON: 39.6 cm x 24.3 cm x 24 cm

- Garage Door Opener Head (1300N)
- Two 4-Button Remote Control (TX4EVF)
- 2-Button Wireless Wall Control (128EV)
- Failsafe Safety Sensor Kit (771EVK)

¹ UK adapter available.

² May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

SAFETY AND SECURITY.

- External Quick Release (optional)
- Automatic Trolley Reconnect
- Down Safety Reverse
- Up Safety Stop
- Flashing Light Connector
- Door-in-Door Connector
- Timer to Close (automatic close) Programming (when safety sensors connected)



LM100EVF MYQ DC GARAGE DOOR OPENER

Maintenance-free, ultra-quiet including LED light.

KEY FEATURES



SPACE-SAVING

Design maximizes versatility

LED LIGHT

LED turns on with activation

LIFTING

For doors up to 150 kg

MYQ

Built In



SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

BELT DRIVE SYSTEM FOR POWERFUL PERFORMANCE.

SOFT-START AND SOFT-STOP FOR SMOOTH OPERATION.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

QUIET AND RELIABLE

QUIET DC MOTOR ELIMINATES NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

HEAVY-LIFTING POWER OPERATES DOORS UP TO 150 KG.

MAINTENANCE-FREE BELT DRIVE ENSURES QUIET & DURABLE OPERATION.

WARRANTY MOTOR: 8 YEARS, CONTROL BOARD: 5 YEARS, ACCESSORIES: 2 YEARS.

SECURE & SAFE

AUTOMATIC GARAGE DOOR OPENERS IMPEDE UNAUTHORIZED ACCESS TO THE GARAGE.

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

EVOLUTION RADIO (SECURITY+ 2.0®) SENDS A NEW CODE WITH EVERY REMOTE CLICK.

AUTOMATIC FORCE SETTING & OBSTACLE DETECTION.

INCLUDED ACCESSORIES:

4-CHANNEL REMOTE CONTROL

Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4EVF

2-BUTTON WIRELESS WALL CONTROL

Operates up to 2 openers. Control your garage door without a remote control.



128EV

POWERFUL ADD-ONS:

INTERNET GATEWAY

MyQ® technology that connects to the internet and allows monitoring and control of the garage door opener.



828EV

GARAGE DOOR MONITOR

MyQ enabled technology allows monitoring and closing up to four garage doors from any room in the house.



829EV

WIRELESS KEYPAD

Provides convenient, secure access from outside the garage with a 4-digit PIN, temporary PIN possible.



747EV

LED FLASHING LIGHT

Lamp flashes while the drive is in action. Applicable for all garage door and gate door openers.



FLA1-LED

FAILSAFE SAFETY SENSOR

2-wire system with LiftMaster signal IP44, range 15 meters.



772E

MASTERFUL ENGINEERING.

MOTOR



- Residential-Duty 24 V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Operating Temperature: -30°C to 55°C

POWER

- 230-240 V AC
- 50/60 Hz Voltage
- 0.8 W Stand-by Power
- 80 cm Power Cord (Euro plug)¹

MECHANICS

- High Quality Chassis and Cover
- Reliable & Quiet Belt Drive Mechanism
- Automatic Force Setting
- Electronic Limits for Easy Setup
- Maintenance-Free Operation thanks to Belt Drive
- 90° Rotation of Power Head for Space Saving



Max. 200 mm


Per second for door to move upward

Max. 200 mm

Per second for door to move downward

STANDARD SPECS.

EVOLUTION RADIO (Security+ 2.0®)



- 4-Button Remote Control (TX4EVF)
- Remote Control: 868 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 433 and 868 MHz
- Copy-Protected Coding

MyQ RADIO



- Provides 2-way communication from garage door opener and MyQ accessories.
- Enables monitoring and control of garage door openers controls via smartphone, tablet or computer.
- Receiver with 180 memory registers.

HOMELINK® COMPATIBLE
(VERSION V OR SOFTWARE REV. 8)²

LIGHTING

LED LIGHT



- LED turns on with activation
- Turns off 2.5 minutes after operation
- 0.8 W Stand-by Power

SHIPPING.

SHIPPING WEIGHT
(in kg)



CARTON: 39.5 cm x 19.5 cm x 24 cm

- Garage Door Opener Head (1000N)
- Two 4-Button Remote Control (TX4EVF)
- 2-Button Wireless Wall Control (128EV)

SAFETY AND SECURITY.

- External Quick Release (optional)
- Automatic Trolley Reconnect
- Down Safety Reverse
- Up Safety Stop
- Flashing Light Connector
- Door-in-Door Connector
- Timer to Close (automatic close) Programming (when safety sensors connected)


¹ UK adapter available.

² May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LM80EVF MYQ DC GARAGE DOOR OPENER

Maintenance-free, ultra-quiet including LED light.

KEY FEATURES



SPACE-SAVING

Design maximizes versatility

LED LIGHT

LED turns on with activation

LIFTING

For doors up to 130 kg

MYQ

Built In



SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

BELT DRIVE SYSTEM FOR POWERFUL PERFORMANCE.

SOFT-START AND SOFT-STOP FOR SMOOTH OPERATION.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

QUIET AND RELIABLE

QUIET DC MOTOR ELIMINATES NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

HEAVY-LIFTING POWER OPERATES DOORS UP TO 130 KG.

MAINTENANCE-FREE BELT DRIVE ENSURES QUIET & DURABLE OPERATION.

WARRANTY MOTOR: 6 YEARS, CONTROL BOARD: 5 YEARS, ACCESSORIES: 2 YEARS.

SECURE & SAFE

AUTOMATIC GARAGE DOOR OPENERS IMPEDE UNAUTHORIZED ACCESS TO THE GARAGE.

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

EVOLUTION RADIO (SECURITY+ 2.0®) SENDS A NEW CODE WITH EVERY REMOTE CLICK.

AUTOMATIC FORCE SETTING & OBSTACLE DETECTION.

INCLUDED ACCESSORIES:

4-CHANNEL REMOTE CONTROL

Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4EVF

2-BUTTON WIRELESS WALL CONTROL

Operates up to 2 openers. Control your garage door without a remote control.



128EV

POWERFUL ADD-ONS:

INTERNET GATEWAY

MyQ® technology that connects to the internet and allows monitoring and control of the garage door opener.



828EV

GARAGE DOOR MONITOR

MyQ enabled technology allows monitoring and closing up to four garage doors from any room in the house.



829EV

WIRELESS KEYPAD

Provides convenient, secure access from outside the garage with a 4-digit PIN, temporary PIN possible.



747EV

LED FLASHING LIGHT

Lamp flashes while the drive is in action. Applicable for all garage door and gate door openers.



FLA1-LED

FAILSAFE SAFETY SENSOR

2-wire system with LiftMaster signal IP44, range 15 meters.



772E

MASTERFUL ENGINEERING.

MOTOR



- Residential-Duty 24 V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Operating Temperature: -30°C to 55°C

POWER

- 230-240 V AC
- 50/60 Hz Voltage
- 0.8 W Stand-by Power
- 80 cm Power Cord (Euro plug)¹

MECHANICS

- High Quality Chassis and Cover
- Reliable & Quiet Belt Drive Mechanism
- Automatic Force Setting
- Electronic Limits for Easy Setup
- Maintenance-Free Operation thanks to Belt Drive
- 90° Rotation of Power Head for Space Saving



Max. 200 mm

Per second for door to move upward


Max. 200 mm

Per second for door to move downward

STANDARD SPECS.

EVOLUTION RADIO (Security+ 2.0®)

High Range:



- 4-Button Remote Control (TX4EVF)
- Remote Control: 868 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 433 and 868 MHz
- Copy-Protected Coding

MyQ RADIO



- Provides 2-way communication from garage door opener and MyQ accessories.
- Enables monitoring and control of garage door openers controls via smartphone, tablet or computer.
- Receiver with 180 memory registers.

HOMELINK® COMPATIBLE
(VERSION V OR SOFTWARE REV. 8)²

LIGHTING LED LIGHT



- LED turns on with activation
- Turns off 2.5 minutes after operation
- 0.8 W Stand-by Power

SHIPPING.

SHIPPING WEIGHT
(in kg)



CARTON: 39.5 cm x 19.5 cm x 24 cm

- Garage Door Opener Head (800N)
- Two 4-Button Remote Control (TX4EVF)
- 2-Button Wireless Wall Control (128EV)

SAFETY AND SECURITY.

- External Quick Release (optional)
- Automatic Trolley Reconnect
- Down Safety Reverse
- Up Safety Stop
- Flashing Light Connector
- Door-in-Door Connector
- Timer to Close (automatic close) Programming (when safety sensors connected)



¹UK adapter available.

²May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LM60EVF MYQ DC GARAGE DOOR OPENER

Maintenance-free, ultra-quiet including LED light.

KEY FEATURES



SPACE-SAVING

Design maximizes versatility

LED LIGHT

LED turns on with activation

LIFTING

For doors up to 100 kg

MYQ

Built In



SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

BELT DRIVE SYSTEM FOR POWERFUL PERFORMANCE.

SOFT-START AND SOFT-STOP FOR SMOOTH OPERATION.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

QUIET AND RELIABLE

QUIET DC MOTOR ELIMINATES NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

HEAVY-LIFTING POWER OPERATES DOORS UP TO 100 KG.

MAINTENANCE-FREE BELT DRIVE ENSURES QUIET & DURABLE OPERATION.

WARRANTY MOTOR: 5 YEARS, CONTROL BOARD: 5 YEARS, ACCESSORIES: 2 YEARS.

SECURE & SAFE

AUTOMATIC GARAGE DOOR OPENERS IMPEDE UNAUTHORIZED ACCESS TO THE GARAGE.

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

EVOLUTION RADIO (SECURITY+ 2.0®) SENDS A NEW CODE WITH EVERY REMOTE CLICK.

AUTOMATIC FORCE SETTING & OBSTACLE DETECTION.

INCLUDED ACCESSORIES:

2-CHANNEL REMOTE CONTROL

Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4EVF

POWERFUL ADD-ONS:

INTERNET GATEWAY

MyQ® technology that connects to the internet and allows monitoring and control of the garage door opener.



828EVF

GARAGE DOOR MONITOR

MyQ enabled technology allows monitoring and closing up to four garage doors from any room in the house.



829EVF

2-BUTTON WIRELESS WALL CONTROL

Operates up to 2 openers. Control your garage door without a remote control.



128EVF

WIRELESS KEYPAD

Provides convenient, secure access from outside the garage with a 4-digit PIN, temporary PIN possible.



747EVF

LED FLASHING LIGHT

Lamp flashes while the drive is in action. Applicable for all garage door and gate door openers.



FLA1-LED

FAILSAFE SAFETY SENSOR

2-wire system with LiftMaster signal IP44, range 15 meters.



772E

MASTERFUL ENGINEERING.

MOTOR



- Residential-Duty 24 V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Operating Temperature: -30°C to 55°C

POWER

- 230-240 V AC
- 50/60 Hz Voltage
- 0.8 W Stand-by Power
- 80 cm Power Cord (Euro plug)¹

MECHANICS

- High Quality Chassis and Cover
- Reliable & Quiet Belt Drive Mechanism
- Automatic Force Setting
- Electronic Limits for Easy Setup
- Maintenance-Free Operation thanks to Belt Drive
- 90° Rotation of Power Head for Space Saving



Max. 160 mm


Per second for door to move upward

Max. 160 mm

Per second for door to move downward

STANDARD SPECS.

EVOLUTION RADIO (Security+ 2.0®)



- 4-Button Remote Control (TX4EVF)
- Remote Control: 868 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 433 and 868 MHz
- Copy-Protected Coding

MyQ RADIO



- Provides 2-way communication from garage door opener and MyQ accessories.
- Enables monitoring and control of garage door openers controls via smartphone, tablet or computer.
- Receiver with 180 memory registers.

HOMELINK® COMPATIBLE (VERSION V OR SOFTWARE REV. 8)²

LIGHTING LED LIGHT



- LED turns on with activation
- Turns off 2.5 minutes after operation
- 0.8 W Stand-by Power

SHIPPING.

SHIPPING WEIGHT (in kg)



CARTON: 39.5 cm x 19.5 cm x 24 cm

- Garage Door Opener Head (600N)
- Two 4-Button Remote Control (TX4EVF)

SAFETY AND SECURITY.

- External Quick Release (optional)
- Automatic Trolley Reconnect
- Down Safety Reverse
- Up Safety Stop
- Flashing Light Connector
- Door-in-Door Connector
- Timer to Close (automatic close) Programming (when safety sensors connected)

¹ UK adapter available.

² May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

EVOLUTION GARAGE DOOR OPENERS.



FEATURES OVERVIEW		LM55EVF	LM60EVF	LM80EVF	LM100EVF	LM130EVF
DOOR WIDTH						
1-PIECE GARAGE DOOR (mm)		3500	5000	5500	5750	6000
SECTIONAL GARAGE DOOR (mm)		3500	5000	5500	5750	6000
CANOPY DOOR (mm)		n/a	3000	3500	3500	4000
DOOR HEIGHT						
1-PIECE GARAGE DOOR		2250	2500	3000	3250	3500
SECTIONAL GARAGE DOOR		2250	2500	3000	3250	3500
CANOPY DOOR		n/a	2500	2500	2500	2500
GARAGE DOOR WEIGHT		90 kg	100 kg	130 kg	150 kg	200 kg
PULLING FORCE MAX. (N)		600	600	800	1000	1300
VOLTAGE		220-240 V AC	220-240 V AC	220-240 V AC	220-240 V AC	220-240 V AC
FREQUENCY		50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
SOFT-START - SOFT-STOP / SPEED MAXIMUM (mm/SEC)		yes / 100	yes / 160	yes / 200	yes / 200	yes / 130
STANDBY POWER CONSUMPTION (WATT)		max. 0.8	max. 0.8	max. 0.8	max. 0.8	max. 0.8
DUTY CYCLE		S2 - 4min	S2 - 4min	S2 - 4min	S2 - 4min	S2 - 4min
WARRANTY / CYCLES (UP/DOWN=1X)		5000	10.000	10.000	15.000	15.000
WARRANTY / YEARS FOR RESIDENTIAL USE		2	5	5	5	5
MOTOR WARRANTY / YEARS FOR THE MOTOR RESIDENTIAL USE		3	5	6	8	10
WARRANTY / YEARS FOR LOGIC BOARD		3	5	5	5	5
ROTATION OF POWER HEAD (SPACE SAVING OPTION)		no	yes	yes	yes	yes
AUTOMATIC LIGHT DELAY		yes 2.5 min	yes 2.5 min	yes 2.5 min	yes 2.5 min	yes 2.5min
ELECTRONIC TRAVEL PROGRAMMING		yes	yes	yes	yes	yes
MYQ SMART PHONE COMPATIBLE (WITH 828EV)		no	yes	yes	yes	yes
GARAGE DOOR MONITORING (UP/DOWN) AUDIBLE & VISIBLE (WITH 829EV)		no	yes	yes	yes	yes
APPLE (IOS), ANDROID COMPATIBLE (OPEN, CLOSE, MONITOR & ALERTS), WITH 828EV		no	yes/free	yes/free	yes/free	yes/free
AUTOMATIC FORCE LEARNING		yes	yes	yes	yes	yes
PUSH BUTTON CONNECTOR		yes	yes	yes	yes	yes
DOOR-IN-DOOR CONNECTOR		no	yes	yes	yes	yes
IR SENSOR CONTACT		yes	yes	yes	yes	yes
FLASHING LIGHT CONNECTOR		no	yes	yes	yes	yes
30V OUTPUT POWER FOR EXTERNAL RECEIVER		yes	yes	yes	yes	yes
UP-STOP-DOWN 2-CHANNEL PROGRAMMING W. TRANSMITTER		no	yes	yes	yes	yes
TIMER TO CLOSE (AUTOMATIC CLOSE) PROGRAMMING (WITH SAFETY SENSORS)		yes	yes	yes	yes	yes
2ND DOOR STOP POSITION PROGRAMMING		no	yes	yes	yes	yes
HOLIDAY MODE (DISABLE OF RADIO) USING 78EV		no	yes	yes	yes	yes
RECEIVER TYPE		EVO,6-Band	EVO,7-Band	EVO,7-Band	EVO,7-Band	EVO,7-Band
MEMORY		40	180	180	180	180
FREQUENCIES		433 & 868 MHz	433 & 868 MHz	433 & 868 MHz	433 & 868 MHz	433 & 868 MHz
TRANSMITTER CODING SCHEME		Evolution Radio (Security+ 2.0®)	Evolution Radio (Security+ 2.0®)	Evolution Radio (Security+ 2.0®)	Evolution Radio (Security+ 2.0®)	Evolution Radio (Security+ 2.0®)
TRANSMITTER TYPE (NUMBER OF CHANNELS)		4	4	4	4	4
RAIL PROFILE IN MM		30	30	30	30	30